

MCHARGER DATASHEET



	Easy C 11 kW	Easy S 11 kW	Easy C 22 kW	Easy S 22 kW	Connected C 22 kW	Connected S 22 kW
Part number	1.801.000	1.801.010	1.801.001	1.801.011	1.801.101	1.801.111
Max. Charging power	11 kW		22 kW			
Input voltage	230 V (1 ph) / 400 V (3 ph) AC					
Rated current	16 A		32 A			
Installation cable	Min. 2,5 mm ²		Min. 6 mm ²			
Mains frequency	50 Hz					
Connection type	Cable 5 m	Socket	Cable 5 m	Socket	Cable 5 m	Socket
Connector plug	Type 2					
Charging mode	3					
Housing dimensions (W x H x D in mm)	266 x 411 x 137 (W x H x D in mm)					
Net weight	5,2 kg	3,0 kg	6,3 kg	3,0 kg	6,3 kg	3,0 kg
Cable entry	top, bottom, rear					
IP protection class	IP55					
Mechanical impact class	IK08					
Surge protection 61010-1	CAT III					
IEC protection class	I					
Operating temperature	-25 °C to +60 °C					
Max. humidity	95 %					
Max. altitude	2000 m					
Certifications	CE RoHS REACH IEC 6100-6-1/61000-6-3 IEC 61851-10 IEC 62196 IEC 62955					
2,4 inch color display	✓					
Acoustic error warning	✓					
DC fault detection 6 mA DC	✓					
Load Balancing	-				✓	
RFID reader	-				✓	
Power limitation	-				✓	
User management	-				✓	